

## ENSURE COMPLIANCE & DOCUMENT RESULTS

DOT MATRIX PRINTERS FOR ALL MODELS OF SARTORIUS BALANCES, SCALES, MOISTURE ANALYZERS & SPECIFIC MODELS OF SPECIFIC BRANDS

- ☀ Do not scrap your existing working weighing device just for password protection.
- ☀ Whether the balance has clock or not generate print outs with date & time
- ☀ Whether the balance has password protection or not protect your documentation from all unauthorized date & time changes
- ☀ Generate Statistics Print out
- ☀ Tare Net Gross Weight Printing
- ☀ Add Alphanumeric Identification to your samples
- ☀ Add your Equipment tag no with all your print outs
- ☀ Initiate Print from balance or Printer
- ☀ Easy to use Keypad



GLP WAY - ejis DOT MATRIX PRINTER

```

-----
Safetab Lifesciences
Bal.Make : Sartorius
Bal.Model: BSA2245
Serial No.:B248568693
S/W Ver.No.:GP-13-11-01
ID : QC
Date :28/Jun/2015
St.Time:16:37:46
AR No. :test-statistics print
W1  + 0.3489g
W2  + 0.3485g
W3  + 0.3483g
W4  + 0.3485g
W5  + 0.3484g
W6  + 0.3485g
W7  + 0.3489g
W8  + 0.3485g
W9  + 0.3489g
W10 + 0.3485g
No.of Wt:10
Sum   : 3.4859g
Avg   : 0.3486g
SD Value : 0.00022g
RSD value : 0.06%
Min.Wt : 0.3483g
Max. Wt : 0.3489g
Range  : 0.0006g
End Time:16:45:47
User Name:Arora
-----
Signature :
    
```

```

-----
Hospira Healthcare India P Ltd
IKKT
-----
Bal.Make : Sartorius
Bal.Model:MwIPI
Serial No.:034483245
S/W Ver.No.:GP-13-11-01
ID : WH/DB/1007
Date :10/Sep/2015
St.Time:15:24:58
AR No. :QC-002300145
Item Code :SVP
Pro. Code :NPNC
Tare wt : 0.200Kg
Nett Wt : 1.202Kg
Gross Wt: 1.402Kg
End Time:15:28:07
User Name:Srinivas
-----
Signature :
    
```

```

-----
2016-03-01 07:49
Sartorius
Mod. MA160-1
SerNo. 0033504602
BAC: 00-53-01
APC: 01-80-01
DOC: 07-40-03
-----
Method name
Standard
Type
Standard drying
Temperature
160 °C
Standby
Off
Initial weight
Off
End
Fully automatic
Result display
Moisture in %M
Target value
Off
No. of filters
0
Start time
07:49
Start weight
+ 2.498 g
Measurement time
02:00 min
Result
0.04 %M
Final weight
+ 2.497 g
Measurement compl.
-----
Name:
    
```

Model : GLP WAY-ejis PRINTER

(Patent Pending)



GLP WAY PRINTER

Printer Unit	Dot matrix printer
Ribbon cartridge	Exchangeable, black ink
Print format	5 x 7, 24-character line length
Print speed	1.2 lines per second
Paper roll	Standard paper 57.5 mm (W), max. Ø 60 mm
Print quality	Thermally stable and light fast paper (GxP)
Print unit durability	1,5 million lines
Power line voltage, frequency	230 VAC, 50/60 Hz
Interface	RS232C, 9pin male connector
Display	3" Colour LCD Display
Enclosure	ABS Plastic
Altitude	Up to 4000 m
Operating temperature	0 - 40 °C Max., 80% at 31 °C, linear decreasing Relative humidity to 50% at 40 °C, noncondensing
Over voltage category	Class II
Included in delivery	Power cable (country specific) Interface cable Paper roll (1 pcs) Ribbon cartridge (1 pcs)
Dimensions	185 mm x 260 mm x 75 mm (WxDxH)
Net weight	600 g (paper roll included)

Manufactured & Marketed by

Distridutor / Dealer

Scouter Engineering Technologies Private Limited,  
#23, St. Thomas Street, Santhosh Nagar,  
Kandanchavadi , Chennai - 600 096.  
Tel : +91 9381206941 & +91 9840172700  
Email : contact@scouter.in  
Skype : scouterindia Website : scouter.in

Subject to Technical changes